


TUPY PIPE FITTINGS - BSP

COUPLER 270



Nominal Diameter		Dimensions in mm	Unitary weight Galvanisation (kg)
in	mm	A	
1/4	8	27	0,030
3/8	10	30	0,042
1/2	15	36	0,063
3/4	20	39	0,094
1	25	45	0,140
1 1/4	32	50	0,195
1 1/2	40	55	0,260
2	50	65	0,388
2 1/2	65	74	0,738
3	80	80	1,080
4	100	94	1,597
6	150	120	4,411

Dimensions:	According to ABNT NBR 6943 , ISO 49 and DIN 2950
Material:	Black Malleable Iron
Surface Protection:	Black or Galvanised according to ABNT NBR 6323
Screw:	BSP according to ISO 7-1, DIN 2999, ABNT NBR 6414
Tolerance Pressure:	According to pressure table

BSP FITTINGS				
Fluid conduction service pressure (According to ISO 49, DIN 2950 and ABNT NBR 6943)				Trial pressure
Temperature		Up to 120°C	Up to 300°C	Ambient
Pressure	lbf/in ² (psi)	360	290	1.500
	kgf/cm ² (bar)	25	20	100
Nominal Size		1/4 to 6		

BACK TO

PLEASE SEE FOLLOWING PAGE FOR FURTHER DETAILS *CATALOGUE*