

TUPY PIPE FITTINGS - BSP MALE-FEMALE 45° BENDS 40



Nominal Diameter		Dimensions in mm		Unitary weight Galvanisation (kg)
in	mm	A	H	
1/4	8	26	21	0,037
3/8	10	30	24	0,058
1/2	15	36	30	0,100
3/4	20	43	36	0,180
1	25	51	42	0,264
1 1/4	32	64	54	0,424
1 1/2	40	68	58	0,532
2	50	81	70	0,858
2 1/2	65	99	86	1,302
3	80	113	100	2,010

Dimensions:	According to ABNT NBR 6943 , ISO 49 and DIN 2950
Material:	Black Malleable Iron
Surface Protection:	Black or Galvanised according to ABNT NBR 6323
Screw:	BSP according to ISO 7-1, DIN 2999, ABNT NBR 6414
Tolerance Pressure:	According to pressure table

P
A
G
E

BSP FITTINGS				
Fluid conduction service pressure (According to ISO 49, DIN 2950 and ABNT NBR 6943)				Trial pressure
Temperature		Up to 120°C	Up to 300°C	Ambient
Pressure	lbf/in ² (psi)	360	290	1.500
	kgf/cm ² (bar)	25	20	100
Nominal Size		1/4 to 6		

BACK TO

PLEASE SEE FOLLOWING PAGE FOR FURTHER DETAILS CATALOGUE