


TUPY PIPE FITTINGS - BSP MALE-FEMALE ELBOWS 92



Nominal Diameter		Dimensions in mm		Unitary weight Galvanisation (kg)
in	mm	A	H	
1/4	8	21	28	0,045
3/8	10	25	32	0,059
1/2	15	28	37	0,102
3/4	20	33	43	0,146
1	25	38	52	0,236
1 1/4	32	45	60	0,371
1 1/2	40	50	65	0,437
2	50	58	74	0,705
2 1/2	65	69	88	1,228
3	80	78	98	1,754

Dimensions:	According to ABNT NBR 6943 , ISO 49 and DIN 2950
Material:	Black Malleable Iron
Surface Protection:	Black or Galvanised according to ABNT NBR 6323
Screw:	BSP according to ISO 7-1, DIN 2999, ABNT NBR 6414
Tolerance Pressure:	According to pressure table

P
A
G
E

BSP FITTINGS				
Fluid conduction service pressure (According to ISO 49, DIN 2950 and ABNT NBR 6943)				Trial pressure
Temperature		Up to 120°C	Up to 300°C	Ambient
Pressure	lbf/in ² (psi)	360	290	1.500
	kgf/cm ² (bar)	25	20	100
Nominal Size		1/4 to 6		

BACK TO

PLEASE SEE FOLLOWING PAGE FOR FURTHER DETAILS CATALOGUE