

TUPY PIPE FITTINGS - BSP

TEE - 130

P
A
G
E

Nominal Diameter		Dimension in mm	Unitary weight Galvanisation (kg)
in	mm	A	
1/4	8	21	0,071
3/8	10	25	0,087
1/2	15	28	0,129
3/4	20	33	0,188
1	25	38	0,311
1 1/4	32	45	0,455
1 1/2	40	50	0,540
2	50	58	0,960
2 1/2	65	69	1,669
3	80	78	2,157
4	100	96	4,026
6	150	131	10,726

Dimensions:	According to ABNT NBR 6943 , ISO 49 and DIN 2950
Material:	Black Malleable Iron
Surface Protection:	Black or Galvanised according to ABNT NBR 6323
Screw:	BSP according to ISO 7-1, DIN 2999, ABNT NBR 6414
Tolerance Pressure:	According to pressure table

BSP FITTINGS				
Fluid conduction service pressure (According to ISO 49, DIN 2950 and ABNT NBR 6943)				Trial pressure
Temperature		Up to 120°C	Up to 300°C	Ambient
Pressure	lbf/in ² (psi)	360	290	1.500
	kgf/cm ² (bar)	25	20	100
Nominal Size		1/4 to 6		

BACK TO

PLEASE SEE FOLLOWING PAGE FOR FURTHER DETAILS CATALOGUE