

TUPY PIPE FITTINGS - BSP

Cap 301



Nominal Diameter		Dimensions in mm	Unitary weight
in	mm	A	Galvanisation (kg)
1/4	8	18	0,022
3/8	10	18	0,030
1/2	15	23	0,047
3/4	20	25	0,071
1	25	29	0,103
1 1/4	32	31	0,181
1 1/2	40	31	0,211
2	50	38	0,325
2 1/2	65	42	0,498
3	80	46	0,733
4	100	56	1,314

Dimensions:	According to ABNT NBR 6943 , ISO 49 and DIN 2950
Material:	Black Malleable Iron
Surface Protection:	Black or galvanised according to ABNT NBR 6323
Screw:	BSP according to ISO 7-1, DIN 2999, ABNT NBR 6414
Tolerance Pressure:	According to pressure table

P
A
G
E

BSP FITTINGS				
Fluid conduction service pressure (According to ISO 49, DIN 2950 and ABNT NBR 6943)				Trial pressure
Temperature		Up to 120°C	Up to 300°C	Ambient
Pressure	lbf/in ² (psi)	360	290	1.500
	kgf/cm ² (bar)	25	20	100
Nominal Size		1/4 to 6		

BACK TO

PLEASE SEE FOLLOWING PAGE FOR FURTHER DETAILS

CATALOGUE