


TUPY PIPE FITTINGS - BSP

Stopper 291



Nominal Diameter		Dimensions in mm		Unitary weight Galvanisation (kg)
in	mm	H	S(max)	
1/4	8	20	8	0,016
3/8	10	20	10	0,018
1/2	15	24	11	0,031
3/4	20	27	17	0,052
1	25	30	19	0,087
1 1/4	32	35	22	0,138
1 1/2	40	36	22	0,176
2	50	45	27	0,289
2 1/2	65	51	32	0,553
3	80	57	36	0,831
4	100	71	41	1,722

Dimensions:	According to ABNT NBR 6943 , ISO 49 and DIN 2950
Material:	Black Malleable Iron
Surface Protection:	Black or galvanised according to ABNT NBR 6323
Screw:	BSP according to ISO 7-1, DIN 2999, ABNT NBR 6414
Tolerance Pressure:	According to pressure table

P
A
G
E

BSP FITTINGS				
Fluid conduction service pressure (According to ISO 49, DIN 2950 and ABNT NBR 6943)				Trial pressure
Temperature		Up to 120°C	Up to 300°C	Ambient
Pressure	lbf/in ² (psi)	360	290	1.500
	kgf/cm ² (bar)	25	20	100
Nominal Size		1/4 to 6		

BACK TO

PLEASE SEE FOLLOWING PAGE FOR FURTHER DETAILS

CATALOGUE