


CUT SPLIT FLANGES



Maximum recommended working pressure kg/cm ²	Nom. flange size in	Type	Dimensions											Weight kg	
			A	B	C	D	E	F	G	H	I	L	M		
		SERIES 3000											Metric	Unc	
345	1/2"	AFS301	30,96	24,26	38,10	54	8,74	22,8	19	13	6,22	8,75	M8x30	5/16 x 1 1/4"	0,12
345	3/4"	AFS302	38,89	32,13	47,63	65	11,13	25,9	22	14	6,22	10,75	M10x35	3/8 x 1 1/2"	0,16
345	1"	AFS303	45,24	38,48	52,37	70	13,08	29,2	24	16	7,49	10,75	M10x35	3/8 x 1 1/2"	0,22
276	1 1/4"	AFS304	51,59	43,69	58,72	79	15,09	36,3	22	14	7,49	12	M10x35	7/16 x 1 3/4"	0,30
276	1 1/4"	AFS304L1075	51,59	43,69	58,72	79	15,09	36,3	22	14	7,49	10,75	M10x35	-	0,30
276	1 1/4"	AFS304L1275	51,59	43,69	58,72	79	15,09	36,3	22	14	7,49	12,75	M12x35	-	0,30
207	1 1/2"	AFS305	61,09	50,80	69,85	94	17,86	41,1	25	16	7,49	13,5	M12x35	1/2 x 1 3/4"	0,43
207	1 1/2"	AFS305L1475	61,09	50,80	69,85	94	17,86	41,1	25	16	7,49	14,75	M14x45	-	0,45
207	2"	AFS306	72,24	62,74	77,77	102	21,44	48,2	26	16	9,02	13,5	M12x35	1/2 x 1 3/4"	0,56
207	2"	AFS306L1475	72,24	62,74	77,77	102	21,44	48,2	26	16	9,02	14,75	M14x45	-	0,50
172	2 1/2"	AFS307	84,94	74,93	88,90	114	25,40	54,1	38	19	9,02	13,5	M12x40	1/2 x 1 3/4"	0,74
138	3"	AFS308	102,39	90,93	106,38	135	30,96	65,3	41	22	9,02	16,75	M16x50	5/8 x 2"	1,30
34	3 1/2"	AFS309	115,10	102,36	120,65	152	34,92	69,5	28	22	10,72	17	M16x50	5/8 x 2"	1,27
34	4"	AFS310	127,79	115,06	130,18	162	38,88	76,0	35	25	10,72	17	M16x50	5/8 x 2"	1,65
34	5"	AFS311	153,19	140,46	152,40	184	46,04	90,0	41	28	10,72	17	M16x50	5/8 x 2"	2,50
		6000 P.S.I.													
420	1/2"	AFS601	32,54	24,64	40,49	56	9,12	23,6	22	16	7,24	8,75	M8x30	5/16 x 1 1/4"	0,16
420	3/4"	AFS602	42,06	32,51	50,80	71	11,91	30,0	28	19	8,26	11	M10x35	3/8 x 1 1/2"	0,34
420	1"	AFS603	48,41	38,86	57,15	81	13,89	34,8	33	24	9,02	13	M12x45	7/16 x 1 3/4"	0,51
420	1 1/4"	AFS604	54,76	44,45	66,68	95	15,88	38,6	38	27	9,78	15*	M14x45	1/2 x 1 3/4"	0,80
420	1 1/2"	AFS605	64,29	51,56	79,38	113	18,26	47,5	43	30	12,07	17	M16x50	5/8 x 2"	1,44
420	2"	AFS606	80,16	67,56	96,82	133	22,23	56,9	52	37	12,07	21	M20x70	3/4 x 2 1/2"	2,10

DESIGNATION FOR ORDER

Only flange

AFS...
AFS...L

With metric screws, grower type washers and o-ring AFS...M

With unc screws, grower type washers and o-ring AFS...U

NOTES

Material: ST52.3

*For unc screws L=13,5

Available in stainless steel AISI 316L.

Superficial coating in yellow galvanising.

[BACK TO](#)
[CATALOGUE](#)