



## PTFE THREAD SEAL TAPE



Performance Plastics are the largest processors of PTFE in Europe and one of the products we manufacture is PTFE Thread Seal Tape.

The sizes available are as follows:-

**STANDARD TAPE - 12m x 12mm x 0.075mm thick**, on all white spools, to **BS7786: 1995 GRADE L**, WRC approved, for use on threads up to a maximum of 15mm diameter. Each spool is printed with the lengths, width and thickness of the tape and the BS Number in order to comply with the BSI. The tape is suitable for use with potable water and conforms to BS6920. Minimum order quantity is 2000 spools.

**SINGLE WRAP (GAS SPECIFICATION) - 5m x 12mm x 0.2mm thick**. To meet requirements of British Gas Specification IM/16, **BS 6974 : 1991**, Corgi and BS 5292 Jointing Materials & Compounds should also be used on threads up to a maximum of 2" Diameter. It is produced on a yellow spool with white outer, printed up with the BS number and the length, width and thickness as specified by the BSI. This is also an ex-stock item. Minimum order quantity is 200 spools.

**SPECIALS - 15m x 25mm x 0.2mm thick** - suitable for sealing the larger threads from 50mm upto 65mm diameter. Available to order - minimum quantities 50 spools.

**SUITABILITY:** All liquids (including oil, diesel etc.) except Oxygen and Fluorine.  
We manufacture a specifically degreased tape for use with Oxygen.

***BACK TO***

**W R C APPROVAL NUMBER - 9210507**

We have facilities for personalised spools.

***CATALOGUE***